

PATENT
450117-03450

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR LETTERS PATENT

TITLE: PORTAL APPLICATION
INVENTORS: Ernö KOVACS, Oliver SCHRAMM, Klaus
RÖHRLE

William S. Frommer
Registration No. 25,506
FROMMER LAWRENCE & HAUG LLP
745 Fifth Avenue
New York, New York 10151
Tel. (212) 588-0800

450117-03450

5

Portal Application

10 The present invention relates to a portal application for providing access from a client to a multimedia service, to a method for accessing a portal application from a client as well as to a multimedia service comprising a portal application.

15 The present invention generally lies in the field of mobile multimedia systems, computer networking, distributed processing systems, databases, hand-held computers and wireless communication. The invention particularly relates to the management of services which can represent the information in different kinds of mark-up languages.

20 Providing mobile internet to cellular phones is possible through the introduction of special adapted web pages. These web pages must be provided through a particular mark-up language (C-HTML in Japan, WAP in Europe, HDML in the USA). The offered services might be the same but differ in presentation and interaction with the user. Providing services to normal web customers but also for mobile users requires the coding of the service for all these different users. If in the future additional further
25 mark-up languages might arise (e.g. in the broadcasting industry) the effort for providing services to users via these further mark-up languages will still increase.

From the prior art so-called service portals are well known. Service portals provide a suit of services of the internet. The basic idea of the service portals is to give the user
30 access to a set of services, so that he will stay longer with the selected portal provider and so that he will return more often.

Mobile service portals are an extension of the service portal idea to wireless internet services. These services are usually provided through special wireless access protocols,
35 but also use mark-up languages that are specially targeted for the mobile device (e.g. Compact HTML in Japan, WAP in the GSM world or HDML in America).

Normally the functions for handling the portal functions (e.g. user identification, service profile, etc.) and the mobile services are directly mixed. For example scripts, graphics and other objects might be stored together.

- 5 Building a mobile service portal requires the provision of an infrastructure of common scripts used by the different services. The set of available services must be managed on a per-user base. Especially free services and subscribed services must be separated and managed individually. Different devices (especially mobile devices) require different mark-up languages for presenting the service to a user. Besides that the used service logic and the components executing the logic should remain the same. Some device types might not support a full range of mark-up tags. In this case the service designer would like to prepare adapted pages optimised just for the targeted device type.

- 10 In view of the above-captioned prior art it is the object of the present invention to present a technique for constructing a portal application and a multimedia service in a flexible and modular way such that the portal application can be scaled up easily by adding further services and such that different mark-up languages can be easily presented.

- 15 According to the invention the presentation (the use of the proper mark-up language) is separated from the logic of the service such that common parts of a service can be reused. This furthermore reduces the time to provide services to different devices.

- 20 According to the invention services can be dynamically installed and removed and the services are supported to produce different kind of mark-up languages for different devices.

- 25 According to the present invention therefore a portal application for providing access from a client to a multimedia service is presented. The portal application comprises a plurality of services respectively structured according to the so-called model-view-controller architecture and respectively comprising at least one model containing data, a controller and at least one view for the presentation of a proper mark-up language. The services are designed to communicate with each other by means of the respective controller.

- 30 A controller can be designed to control at least one further controller of another or the same service.

In the following further advantages, features and objects of the present invention will become evident for the man skilled in the art by means of a detailed explanation of embodiments of the present invention taken in conjunction with the figures of the enclosed drawings.

5

Figure 1 shows the framework of the present invention,

10

Figure 2 shows the internal structure of a service conforming to the MVC (model-view-controller) architecture,

15

Figure 3 shows the relation between an application according to the present invention on top of a middleware,

20

Figure 4 shows the structure of services according to the present invention communicating via the controller of the service, wherein a plurality of views can be associated with one controller,

25

Figure 5 shows schematically the procedure to build up an interaction between the browser of a client and a special (mobile) service,

Figure 6 shows a dialog sequence according to the present invention,

Figure 7 shows states of a controller dependent on the presentation language, and

Figure 8 shows a graphical representation of a controller state depending on a plurality of criteria such as location and used mark-up language.

30

With reference to figure 1 the framework of the present invention will be explained.

35

By means of a network such as for example the internet clients 11 with browser can access a multimedia service 1. The multimedia service 1 is built on top of a middleware 2 which can comprise a user profile database 3 and a service profile database 4.

The multimedia service 1 is built up of a plurality of services, which can be generally divided into management and administration related core services, such as a portal 5, a user management service 6 and a service management 7 and special services such as a mail service 8, a mailbox service 9 and a download service 10.

Separation of Concern

The different aspects of a service are clearly separated. The controller object receives the object, analyses the request, analyses the status of the interaction and checks for information about the browser, the type of requested mark-up. Based on this information it selects an available view object.

This view object does not have to care for these details, but prepares the information page that is displayed to the user. Through the JSP concept, mark-up language and service logic is clearly separated.

Finally, the service logic and data handling parts of the service is executed by model components which can be written f.e. in Java and might access databases or perform the requested functions.

Uniform Service Structure

The selected schema enforces a uniform service structure.

20 Different Views for different Situations

Having different views that are dynamically selected through the controller makes it easier to provide different output for different devices and mark-up languages.

25 Communication between different services is realised by JAVA servlets' communication facilities. Java server pages are dynamically compiled to Java servlets. Browser requests are forwarded between the servlets.

Usage of Mobile Middleware

One part of the invention is to apply these kinds of techniques to manage the life cycle of services. To get an clear understanding, figure 2 shows the basic relation between the MVC pattern and JAVA servlets.

35 In terms of the normal MVC design pattern, the model is a data container, which can be accessed to gain information to represent this in a view. The framework extends the functionality of a model by a middleware concept. As outlined in figure 3 the model might be a normal data container, or it can offer middleware functionality to services.

5

Framework Services

15

20

25

30

35

Special services can be added and deleted on the fly. Examples for special services are:

Instant Message Broker Service

- 5 A message allowing to enter instant messages and to send them to mobile users. Instant messages might be converted to short messages and sent to the GSM phone of the target user.

Instant Message Box

- 10 The instant message box contains copies of messages that are sent to the user. The user might configure his system so that every message or only a subset of messages are stored in the instant message box.

Electronic Content Sales Service

- 15 A service selling electronic content (e.g. games, music, video, ...).

Further Advantages

- 20 One advantage of the selected technologies is that since all components are written in JAVA they can migrate between different virtual machines. This allows for dynamic load balancing.

- 25 The main issue targeted by our service framework, and the most important part of our invention, is that the service framework is very scaleable and it is very easy to handle distributed mobile services in this service framework. Especially it is quite easy to add or remove services from the service framework.

- 30 The scalability and flexibility is gained through merging of the controlling concept of the MVC pattern and the servlet's communication mechanism. A user-agent's request can be conditionally forwarded or redirected to specific services which itself can forward the request to other, maybe more specific, services.

- 35 Figure 4 shows that a multimedia service and particularly a portal application according to the present invention is constructed in a modular way. Further services can be added easily, as the controller units 13 of a service are respectively designed for a direct communication with each other.

One controller 13 of a service can be associated with a plurality views 12, 12', 12'' for representing the same data of the model component 14 with different mark-up languages. In other words, each of the views 12, 12', 12'' is responsible for the representation of a data of the model component 14 with a particular mark-up language.

5

As can be seen from figure 5, the interaction between a client with a browser 11 and a mobile service 8, 9 can be divided into two steps: At first the client 11 sends a request to one of the core services 5, 6 which are responsible for administrative and management purposes. The request is for example processed by a portal core service 5 which exchanges data with a user management core service 6 for example to check the identity of the client with a browser 11 and to validate passwords etc. The request is furthermore forwarded to a special service such as a mail service mobile service 8 in case the interaction of the portal core service 5 with the user management core service 6 in step 2 had a positive result. Once the request of the browser 11 of the client has been passed and processed through the portal core service 5 the further interaction then takes place directly between the client 11 and the browser and the dedicated special mobile service 8, 9.

10

15

Figure 5 outlines the basic idea of forwarding based on the MVC's controller.

20

To summarise the interaction:

25

- (1) The portal service's controller receives a request from an user-agent (browser).
- (2) The portal service's controller validates the request with the help of the user management service.
- (3) The portal service's controller forwards the request to the IMail service's controller.
- (4) The IMail service's controller sends a response to the user-agent.

30

Based on the JAVA servlet's technology the services need not reside on the same JAVA servlet engine.

Generating of different presentation languages

35

Each graphical user interface interaction can be split up into separate steps. These steps can be described by a finite state machine.

As mentioned above all services are conform to the MVC pattern. By designing the controller as a finite state machine the steps of interaction can be steered by such a controller.

0969549-070304

A controller is, conform to the MVC pattern, also responsible to select the appropriate presentation (view). Based on the requested format it can decide which kind of presentation language is convenient for the user's agent requests.

5

Figure 6 demonstrates how this interaction can work. The context of this scenario is to send a message and therefore the sender has to select a specific address, insert a specific message - and at the end the user receives a positive or negative acknowledgement dependent whether the message has been sent successfully or not.

10

All rectangles represent information in a specific mark-up language like XHTML or WML. Dependent on the user-agents request a service's controller can determine which presentation mark-up can be presented by the user's user-agent. Based on this information the controller can determine in which presentation language the content must be sent.

15

An advanced feature of this invention is that the finite state machine can be extended to use sub-finite state machines. This is important when the representation of the business content depends on the used representation language. E.g. there are different dialogs for user interfaces written in XHTML and WML.

20

Figure 7 shows different finite state machines. In the case a user-agent can only represent WML the controller uses a subset B1, B2, B3 of the available states as in the case of using HTML. This may vary dependent on the presentation language.

25

Figure 8 summarises the relation between the amount of presentation languages and dialog steps, realised by a finite state machine in the service's controller.

Criteria for the Selection of a Presentation Format

30

Besides the selection of an appropriate mark-up language for the client device, the controller may also take other criteria into account. A service may for example specify different presentations for different times of the day or in different languages. Or if there is information about a specific user (users must login to the system) the service may want to adapt to user preferences e.g. it may use bigger fonts for visually impaired users.

35

These presentations may not differ in their service relevant content but vary according to other criteria. Such criteria could be

- browser characteristics
- device characteristics (e.g. screen size)
- time/date
- 5 • language
- user preferences

Of course it is hard for a service developer to develop presentations for all different combinations of possible criteria. Therefore the service may want to add filters which

10 can convert a given presentation into a different format (this is not possible with all formats e.g. automatic translation of pages is still not possible in good quality). Such filters can be easily added to the service framework (they may also be part of the middleware). The process of selecting a suitable presentation format then involves to select an appropriate base format according to a subset of the relevant criteria (these

15 base formats still have to be developed) and then an adaptation using filter mechanisms to meet the missing criteria.

10.00.00 01500000